



SDH-EM 1500, SDH-2500, SDH-EM 2500

Item #	Max Def. (in)	A (in)	H (in)	K (in)	G (in)	d (in)	D (in)	** Max. Load / Rubber Hardness			
								40 Sh. (lbs.)	50 Sh. (lbs.)	60 Sh. (lbs.)	70 Sh. (lbs.)
<b>***** 2-Hole Base Mounts*****</b>											
SDH-B	0.12	3.0	1.3	3.7	M12	0.38	1.9	154	231	286	*
SDH-EM 40	0.16	3.5	1.4	4.3	M10	0.35	2.5	66	99	143	165
SDH-40	0.10	3.5	1.4	4.3	M10	0.35	2.5	154	286	374	539
SDH-EM 60	0.20	3.9	1.4	4.7	M12	0.43	2.5	110	165	264	308
SDH-100	0.12	4.3	1.2	5.1	M10/12	0.35	3.1	242	354	508	660
SDH-EM 125	0.22	4.3	1.4	5.1	M10/12	0.35	3.3	176	286	385	517
SDH-200	0.14	4.8	1.4	5.9	M10/12	0.39	3.7	396	506	594	725
SDH-350	0.14	5.5	1.5	6.7	M12/16	0.50	4.2	550	770	990	1210
SDH-EM 350	0.28	5.5	1.6	6.7	M12/16	0.50	3.8	440	671	925	1100
SDH-500	0.20	6.1	1.7	7.6	M16	0.55	4.9	990	1210	1515	1980
SDH-800	0.28	7.2	1.9	8.5	M16	0.55	5.7	990	1650	2860	*
SDH-EM 800	0.35	7.2	2.1	8.6	M16	0.57	5.9	990	1254	1425	2200
<b>***** 4-Hole Base Mounts*****</b>											
SDH-EM 1500	0.60	5.8	3.4	7.1	M20	0.57	7.2	1925	*	3740	*
SDH-2500	0.28	7.1	4.1	8.7	M24	0.69	8.7	3080	5280	6160	10780
SDH-EM 2500	0.63	7.1	4.1	8.7	M24	0.69	8.7	3520	5280	7480	9240

\*\* Each part is made with 3 or 4 different rubber hardnesses (i.e. 40, 50, 60, 70 shore hardness)